

Drive hard profits
with soft signs.

VUTEk® FabriVU 180/340



At a glance

- 1.8-meter and 3.4-meter wide aqueous-based soft signage printer models
- Dramatic four-color printing with a wide color gamut and deep color saturation for exceptional fabric display graphics
- Ultra-high resolution up to 2,400 dpi and four level grayscale printing with 4pL to 18pL drop sizes
- Ideal for the production of flags, banners, backlit displays, and other high-end display graphics
- Print direct to textile or transfer paper with the ability to changeover from one to the other
- Auto print head cleaning station increases printer uptime
- Capping station to keep your system up and running
- Patented ink recirculation system for improved ink yield
- Wrinkle detect system protects against costly repairs due to head strikes



EFI VUTEk FabriVU 180

Media/Handling

- Prints up to 70 in (180 cm) wide
- Fabric weight from 45 to 450 gr/m²
- Paper weight from 28 to 140 gr/m²
- Entry and exit: standard roll unwinder/rewinder up to 17.5 in (450 mm) outside diameter
- Dryer: heated platen

Resolution

Up to 2,400 dpi

Productivity

- Production speeds (max.) up to 4,305 ft² (400 m²) per hour
- Production image quality: 2,152 ft² (200 m²) per hour
- POP image quality: 1,420 ft² (132 m²) per hour

Formats

All popular desktop file formats, including PostScript®3™, EPS, TIFF, PDF, RGB/CMYK

Environmental considerations

- Temperature: 68-75 °F (20-24 °C)
- Humidity: 50-60%
- Weight: 6,613 lbs (3000 kg)

- Printer, platen, and winders dimensions (L x W x H): 90 in x 178 in x 71 in (230 cm x 454 cm x 180 cm)
- Printer electrical: 3 Phase, 400V, 50Hz, 35kW
- Water pressure: min. 22 psi (1.5 bar); max. 29 psi (2 bar)
- Water volume: 1.3 gallons (5 liters) per hour
- Water temperature: 68-77 °F (20-25 °C)

Genuine EFI Inks

Water based CMYK dispersed dye inks



EFI VUTEk FabriVU 340

Media/Handling

- Prints up to 133 in (340 cm) wide
- Fabric weight from 45 to 450 gr/m²
- Paper weight from 28 to 140 gr/m²
- Entry and exit: standard roll unwinder/rewinder up to 17.5 in (450 mm) outside diameter
- Dryer: heated platen

Resolution

Up to 2,400 dpi

Productivity

- Production speeds (max.) up to 5,381 ft² (500 m²) per hour
- Production image quality: 2,690 ft² (250 m²) per hour
- POP image quality: 1,776 ft² (165 m²) per hour

Formats

All popular desktop file formats, including PostScript[®]3™, EPS, TIFF, PDF, RGB/CMYK

Environmental considerations

- Temperature: 68-75 °F (20-24 °C)
- Humidity: 50-60%
- Weight: 10,582 lbs (4,800 kg)

- Printer and dryer dimensions (L x W x H): 90 in x 242 in x 71 in (230 cm x 615 cm x 180 cm)
- Printer electrical: 3 Phase, 400V, 50Hz, 35kW
- Water pressure: min. 22 psi (1.5 bar); max. 29 psi (2 bar)
- Water volume: 1.3 gallons (5 liters) per hour
- Water temperature: 68-77 °F (20-25 °C)

Genuine EFI Inks

Water based CMYK dispersed dye inks



ARROW DIGITAL PVT. LTD.

1005-1006, Aditya - 10th Floor Opp. Sardar Patel Seva Samaj Chimanlal Girdharlal Road Mithakhali, Navrangpura, Ahmedabad - 380006. Gujarat - India. Tel: +91 79 2640 4017 / 18, +91 79 2640 5048 / 49

Demo Center - Ahmedabad

Branches - Delhi, Mumbai, Indore, Bangalore, Kolkata, Pune, Hyderabad, Chandigarh, Chennai

www.arrow-digital.com

sales@arrow-digital.com

Connect with us on...

