

Soft signage that fits your needs

VUTEk® FabriVU 340i



***Lower total acquisition cost. Fast job turns. More premium-margin capability.
It's soft signage printing for the rest of us.***

When you want to offer soft signage but don't have the higher volumes, floor space, or capex spend to justify a soft signage printer —let alone a dedicated calender/heat press— you get a soft signage printer that fits your needs. Not the other way around.

The EFI™ VUTEK® FabriVU 340i dye-sublimation printer offers production level speeds, outstanding image quality, and inline fixation capability. It allows you to direct print to fabric and sublimate inline for one-offs that are immediately ready for finishing and shipping.

At a glance

- 3.4-meter wide aqueous-based soft signage printer with new EFI platen and extraction technology system that enables product to be sublimated inline
- Dramatic four-color printing with a wide color gamut and deep color saturation for exceptional fabric display graphics
- Ultra-high resolution up to 2,400 dpi and four level grayscale printing with 4pL to 18pL drop sizes
- Production speeds up to 2,691 ft² (250 m²) per hour
- Prints direct to fabric with inline fixation for graphics that are immediately ready for finishing and packing
- Inline sublimation can be turned off and paper transfer can be leveraged if off-line sublimation is available
- Ideal for the production of flags, banners, backlit displays, and other high-end display graphics, including one-offs
- Auto printhead cleaning station increases printer uptime
- Capping station to keep your system up and running
- Medium viscosity ink, high-resolution printheads, and ink recirculation system for improved ink yield



Applications

- Banners
- Flags
- Furnishings
- Soft signage
- Wall coverings



EFI VUTEk FabriVU 340i

Media/Handling

- Prints up to 133 in (340 cm) wide
- Fabric weight from 45 to 450 gr/m²
- Paper weight from 57 to 110 gr/m²
- Entry and exit: standard roll unwinder/rewinder up to 13.75 in (350 mm) outside diameter
- Inline sublimation: heated platen

Resolution

- Up to 2,400 dpi

Productivity

- Production speeds (max): up to 5,381 ft² (500 m²) per hour² (400 m²) per hour
- Production image quality: 2,690 ft² (250 m²) per hour² (200 m²) per hour
- POP image quality: 1,776 ft² (165 m²) per hour² (132 m²) per hour

Formats

- All popular desktop file formats, including PostScript® 3™, EPS, TIFF, PDF, and RGB/CMYK

Environmental considerations

- Temperature: 68-75 °F (20-24 °C)
- Humidity: 50-60%
- Weight: 10,582 lbs (4,800 kg)
- Printer and dryer dimensions (L x W x H): 90 in x 242 in x 71 in (230 cm x 615 cm x 180 cm)
- Printer electrical: 3 Phase, 400V, 50Hz, 42kW
- Water pressure: min. 22 psi (1.5 bar); max. 29 psi (2 bar)
- Water volume: 1.3 gallons (5 liters) per day
- Water temperature: 68-77 °F (20-25 °C)

Genuine EFI Inks

- Water-based CMYK-dispersed dye inks



Arrow Digital Pvt. Ltd.

827, Pramukh Estate, Behind Prima Automation, Rakanpur, Ahmedabad, Gujarat, India - 382721.
Tel. : +91 70411 26568, +91 70411 26454

Arrow Digital Innovation Center - Ahmedabad

Branches : Ahmedabad, Bengaluru, Delhi, Indore, Kolkata, Mumbai, Pune, Surat

Follow us on:      

www.arrow-digital.com sales@arrow-digital.com